

ROTAVATOR | B-36




Model	B36	155	180	205	230	255
Dimension, mm (L x W x H)	1805 x 1025 x 1100	2060 x 1025 x 1100	2315 x 1025 x 1100	2570 x 1025 x 1100	2825 x 1025 x 1100	
Working Width, cm	155	180	205	230	255	
For Tractor, Hp	55-60hp	60-75hp	70-90hp	90-110hp	90-110hp	
3-Point Linkage, CAT				I/II		
Universal Driveshaft				A8 c/w FF4 Slip Clutch		
Gearbox				Multi Speed		
No of Flanges	7	8	9	10	11	
No of Blades	36	42	48	54	60	
Size of Blades, mm			80 x 7			
Rotor Speed at 540 rpm			166 / 203 / 144 / 235			
Side Transmission Drive			Rollerchain & Sprocket			
Max Working Depth, cm			18			
Type of Blade			L or C (Optional)			
Weight (kg)	470	510	550	590	630	

L / C Blade



Face Seal



Multi Speed Gear

PTO Drive Shaft



This extra-heavy-duty rotavator performs excellently in demanding conditions and is ideal for “built-on” combinations - such as Ripper, Furrower or Crumble Roller.

Side drive through heavy-duty Roller Chain - 17 ton breaking load - with externally adjustable tensioning skid. Rotor drive is supported by large ball bearings and face seals.

Protection of tractor and transmission against shock-loads ensured by heavy - duty safety clutch.

Cultivating depth is adjustable - raising-lowering the side skids.

Depth control wheels available as optional.

Selectatilt pick- off gears allow four alternative rotor speeds (540 PTO)

